



MODEL SLX400E SPECIFICATIONS

Due to continual product improvements all specifications are subject to change without notice.

| Weights | lbs. | kgs. |
|-------------------|---------------|--------------|
| Net | 470 | 213 |
| Crated | 568 | 257 |
| | cu.ft. | cu.m. |
| Volume | 58.42 | 1.65 |
| Dimensions | in. | cm |
| Width | 22-1/8 | 56.20 |
| Depth | 30-1/8 | 76.52 |
| Height | 60-11/16 | 154.15 |

| Electrical | Maximum Fuse Size | NEMA Plug Type | | |
|--------------------|--------------------------|-----------------------|------------------|------------------|
| 208-230/60/1 Air | 16 | 6-20P | | |
| 208-230/60/1 Water | 16 | 6-20P | | |
| | Total Amps (Qty) | kW | Poles (P) | Wires (W) |
| 220-240/50/1 Air | 15.0 | 3.1 | 2P | 3W |
| 220-240/50/1 Water | 15.7 | 3.2 | 2P | 3W |

Electrical characteristics other than above available on request from factory or local distributor. Check nameplate for exact electrical data.

Bidding Spec

Electrical: Volt _____ Hz _____ Ph _____
 Cooling: _____ Neutral _____ Yes _____ No
 Options: _____

Electrical

One dedicated electrical connection is required. 60 Hertz units connects to a standard NEMA 6-20R receptacle. See electrical chart for the proper requirement. Consult your local electrical codes for cord and receptacle specifications.

Beater Motor

Two, 1 hp.

Refrigeration Systems

One, 6,900 Btuh. R404a.
 Btuh may vary depending on compressor used.

Air Cooled

6" (15.2 cm) air space required on rear panel for proper air circulation and be open on the top.

Mix Hopper Capacity: two - 12 quarts (11.4 liters) each
Freezing Cylinder Capacity: two - 2.7 quarts (2.6 liters) each

Certified and/or listed by:



*UL listed and listed by Underwriters Laboratories under Canadian National Standard C22.2 No. 120-M91 (R2008)

**Selected voltages only. Contact H.C. Duke to verify agency needs.